

Cambridge O Level

COMPUTER SCIENCE**2210/22**

Paper 2 Algorithms, Programming and Logic

May/June 2026**MARK SCHEME**Maximum Mark: 75

Published

This mark scheme contains the instructions and marking guidance that our examiners used to mark candidate responses for this component.

Before they start marking, examiners complete a standardisation process. They review a range of candidate responses and discuss the mark scheme in detail to agree which answers can and cannot be accepted. Examiners award marks where it is clear that candidate responses have met the requirements of the mark scheme. These requirements may vary between different components or different versions of the same component, depending on the exact requirements of the question and the candidate responses seen during the standardisation process.

Sometimes, our mark schemes may allow marks to be awarded to responses which contain elements that are factually incorrect or for content not covered by the syllabus. We do this in response to the demands of a specific question to support candidates and make sure that our assessments are fair. However, these allowances should not be used as a guide for teaching and learning.

We cannot discuss the mark scheme with schools, and we recommend that schools read the mark scheme together with the assessment material and the Principal Examiner Report for Teachers.

This document consists of **24** printed pages.

General marking principles

All examiners must apply these marking principles when marking candidate responses.

1	Examiners must award marks for each response in line with: - the specific content defined in the mark scheme - the specific skills defined in the mark scheme or in the level descriptions - the standard of response required as exemplified by the standardisation scripts.
2	Examiners must award whole marks (not half marks, or other fractions).
3	Examiners must award marks positively . This means that: - marks are not deducted for errors or omissions - marks are awarded for correct/valid answers as defined in the mark scheme and also for other valid answers which go beyond the scope of the syllabus and mark scheme referring to your team leader as appropriate - the quality of spelling, punctuation and grammar are judged only when the mark scheme indicates that these features are specifically assessed in the question. However, the meaning of all responses must be unambiguous.
4	Examiners must consistently apply the requirements of the mark scheme and any rules for what to do when candidates have not followed instructions correctly.
5	Examiners must use the full range of marks defined in the mark scheme, unless limited by the quality of the candidate responses seen.
6	Examiners must award marks according to the mark scheme and must not award marks with grade thresholds or grade descriptions in mind.

Annotations guidance for centres

Examiners use a system of annotations as a shorthand for communicating their marking decisions to one another. Examiners are trained during the standardisation process on how and when to use annotations. The purpose of annotations is to inform the standardisation and monitoring processes and guide the supervising examiners when they are checking the work of examiners within their team. The meaning of annotations and how they are used is specific to each component and is understood by all examiners who mark the component.

We publish annotations in our mark schemes to help centres understand the annotations they may see on copies of scripts. Note that there may not be a direct correlation between the number of annotations on a script and the mark awarded. Similarly, the use of an annotation may not be an indication of the quality of the response.

The annotations listed below were available to examiners marking this component in this series.

Annotations

Annotation	Meaning
	Correct point
	Incorrect point
	Follow through
	Repetition
	Ignore
	Benefit of doubt given
	Content of response too vague
	Not answered question
	Omission
	Section not relevant

Annotation	Meaning
	Section incorrect
Highlighter	Highlights part of the answer or shows structure of complex answers
SEEN	Page or response seen by examiner
A2	AO2 mark
A3	AO3 mark
NE	Not enough
R1	Required item one
R2	Required item two
R3	Required item three
 1	Correct awarding one mark
 2	Correct awarding two marks
 3	Correct awarding three marks
 4	Correct awarding four marks
 5	Correct awarding five marks
 6	Correct awarding six marks
 7	Correct awarding seven marks
 8	Correct awarding eight marks
 9	Correct awarding nine marks

Mark scheme abbreviations

/ separates alternative words / phrases within a marking point

// separates alternative answers within a marking point

underline actual word given must be used by candidate (grammatical variants accepted)

max indicates the maximum number of marks that can be awarded

() the word / phrase in brackets is not required, but sets the context

Note: No marks are awarded for using brand names of software packages or hardware

Question	Answer	Marks	Guidance
1	C	1	

Question	Answer	Marks	Guidance
2	B	1	

Question	Answer	Marks	Guidance
3(a)(i)	Presence (check)	1	
3(a)(ii)	Check digit	1	
3(b)	One mark each - To check that the input matches a specified / required style / pattern / structure ... by containing set numbers of letters and numbers // ... by containing specified groups of digits // ... by containing specific characters within the text - An example of a format e.g. date format dd/mm/yyyy	3	BOD for arrangement Allow an @ within an email address as an example

Question	Answer	Marks	Guidance
3(c)	One mark each • Appropriate loop to iterate for 15 inputs • Input of a number • Test if the input is an integer e.g. use of MOD, DIV or ROUND functions • Repeated re-input if number not an integer, until it is an integer • Store integer in the correct array location • At least two outputs seen, from input prompt / error message / completion message. For example: <pre> FOR Counter ← 1 TO 15 REPEAT OUTPUT "Input a whole number" INPUT Value IF MOD(Value,1) <> 0 // IF ROUND(Value,0) <> Value // IF DIV(Value,1) <> Value THEN OUTPUT "Your number was not an integer, please re- input" ELSE Accepted[Counter] ← Value ENDIF UNTIL MOD(Value, 1) = 0 NEXT Counter OUTPUT "The check has been completed" </pre>	6	No array or variable declarations required for this algorithm Accept other methods for testing if a number is an integer Ignore case

Question	Answer	Marks	Guidance
4	One mark per mark point for coding, max three • Writing the program code in a programming/coding language • ... using pseudocode/flowcharts/structure diagrams from the design/earlier stage to create your code • Documenting your code with comments // making sure your code is maintainable • Writing procedures/functions // Use library routines/functions • Using a compiler/interpreter/IDE when writing the code • Testing the code in small parts as you write it allow iterative testing • ... to ensure that it works correctly / as expected // ... to refine your code One mark per mark point for testing, max three • The final stage of testing the whole program for errors • Use of test data with known outcomes • ... to ensure the whole program produces the expected outcomes (from the test data) // ... to make sure the program accepts valid data and rejects invalid data • Correct errors // debug the code • Allow one mark max for identifying at least two types of test data e.g. normal, abnormal, boundary, extreme	6	Allow use of test data as BOD for MP9

Question	Answer	Marks	Guidance
5(a)	One mark per mark point, max four - Line 03 / DECLARE AccountID : INTEGER should be DECLARE AccountID : STRING - Line 05 / OUTPUT AccountID should be INPUT AccountID - Line 07 / CASE OF AccountID = Accounts[Row, 1] should be IF AccountID = Accounts[Row, 1] - Line 09 / OUTPUT "The customer's name is ", Accounts[1, 2] should be OUTPUT "The customer's name is ", Accounts[Row, 2] <pre> 01 DECLARE Accounts : ARRAY[1:1000, 1:2] OF STRING 02 DECLARE Row : INTEGER 03 DECLARE AccountID : STRING 04 OUTPUT "Please enter an account ID " 05 INPUT AccountID 06 FOR Row ← 1 TO 1000 07 IF AccountID = Accounts[Row, 1] 08 THEN 09 OUTPUT "The customer's name is ", Accounts[Row, 2] 10 ENDIF 11 NEXT Row </pre>	4	Ignore case
5(b)	Linear search	1	Accept sequential search

Question	Answer	Marks	Guidance
5(c)	Adding to the existing corrected algorithm Any five from: • Use/initialise a flag at the start / before line 06 • Flag ← FALSE // Flag ← 0 • Between lines 08 and 10 (where the item has been found) • Flag ← TRUE // Flag ← 1 • Outside the loop / after line 11 add another selection statement and output • IF Flag = False ... • ... <u>THEN</u> OUTPUT "Account number not found in the array" <u>ENDIF</u> For example: <pre> 01 DECLARE Accounts : ARRAY[1:1000, 1:2] OF STRING 02 DECLARE Row : INTEGER 03 DECLARE AccountID : STRING DECLARE Flag : BOOLEAN Flag ← FALSE 04 OUTPUT "Please enter an account ID " 05 INPUT AccountID 06 FOR Row ← 1 TO 1000 07 IF AccountID = Accounts[Row, 1] 08 THEN 09 OUTPUT "The customer's name is ", Accounts[Row, 2] Flag ← TRUE 10 ENDIF 11 NEXT Row IF Flag = FALSE THEN OUTPUT "Account number not found in the array" ENDIF </pre>	5	If no location is given, Max 1 for each of MP1/2 or MP3/4 or Max 2 for MP5/6/7. The locations stated in the mark points are for the use of examiners. Any line numbers quoted within these ranges, inclusive, are accepted. If a correct location is clearly identified descriptively without using line numbers, award the mark. Ignore case


Question	Answer	Marks	Guidance
5(c)	OR replacing FOR loop with a WHILE loop Any five from: • Use/initialise a flag at the start / before line 06 • Flag ← FALSE // Flag ← 0 • Between lines 08 and 10 (where the item has been found) • Flag ← TRUE // Flag ← 1 • Outside the loop / after line 11 add another selection statement and output • IF Flag = False ... • ... THEN OUTPUT "Account number not found in the array " ENDIF • Replace lines 06 and 11 and increment counter before line 11 • WHILE NOT Flag AND Row ≤ 1000 (DO) • Row ← Row + 1 and ENDWHILE For example: <pre> 01 DECLARE Accounts : ARRAY[1:1000, 1:2] OF STRING 02 DECLARE Row : INTEGER 03 DECLARE AccountID : STRING DECLARE Flag : BOOLEAN Row ← 1 Flag ← FALSE 04 OUTPUT "Please enter an account ID " 05 INPUT AccountID 06 WHILE NOT Flag AND Row ≤ 1000 (DO) 07 IF AccountID = Accounts[Row, 1] 08 THEN 09 OUTPUT "The customer's name is ", Accounts[Row, 2] Flag ← TRUE 10 ENDIF Row ← Row + 1 </pre>		If no location given, Max 1 for each of MP1/2 or MP3/4 or Max 2 for MP5/6/7 Max 2 or MP8/9/10. The locations stated in the mark points are for the use of examiners. Any line numbers quoted within these ranges, inclusive, are accepted. If a correct location is clearly identified descriptively without using line numbers, award the mark. Ignore case

Question	Answer	Marks	Guidance
5(c)	<pre>11 ENDWHILE IF Flag = FALSE THEN OUTPUT "Account number not found in the array" ENDIF</pre>		

Question	Answer	Marks	Guidance																																																																																																																		
6(a)	One mark for each correct column <table><tr><th>Word</th><th>WordLength</th><th>Count</th><th>NumLetter</th><th>Choice</th><th>OUTPUT</th></tr><tr><td>post</td><td>4</td><td>0</td><td>1</td><td></td><td></td></tr><tr><td></td><td></td><td></td><td>2</td><td></td><td></td></tr><tr><td></td><td></td><td></td><td>3</td><td></td><td></td></tr><tr><td></td><td></td><td></td><td>4</td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td>Y</td><td>0</td></tr><tr><td>committee</td><td>9</td><td>0</td><td>1</td><td></td><td></td></tr><tr><td></td><td></td><td></td><td>2</td><td></td><td></td></tr><tr><td></td><td></td><td>1</td><td>3</td><td></td><td></td></tr><tr><td></td><td></td><td></td><td>4</td><td></td><td></td></tr><tr><td></td><td></td><td></td><td>5</td><td></td><td></td></tr><tr><td></td><td></td><td>2</td><td>6</td><td></td><td></td></tr><tr><td></td><td></td><td></td><td>7</td><td></td><td></td></tr><tr><td></td><td></td><td>3</td><td>8</td><td></td><td></td></tr><tr><td></td><td></td><td></td><td>9</td><td></td><td>3</td></tr><tr><td></td><td></td><td></td><td></td><td>N</td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>	Word	WordLength	Count	NumLetter	Choice	OUTPUT	post	4	0	1						2						3						4							Y	0	committee	9	0	1						2					1	3						4						5					2	6						7					3	8						9		3					N																				6	If no other marks awarded, allow 1 mark for correct first initialisation of <code>Count</code> and <code>NumLetter</code> to 0 and 1 respectively FT for the <code>OUTPUT</code> column for candidate's <code>Count</code> final values for each word
Word	WordLength	Count	NumLetter	Choice	OUTPUT																																																																																																																
post	4	0	1																																																																																																																		
			2																																																																																																																		
			3																																																																																																																		
			4																																																																																																																		
				Y	0																																																																																																																
committee	9	0	1																																																																																																																		
			2																																																																																																																		
		1	3																																																																																																																		
			4																																																																																																																		
			5																																																																																																																		
		2	6																																																																																																																		
			7																																																																																																																		
		3	8																																																																																																																		
			9		3																																																																																																																
				N																																																																																																																	

Question	Answer	Marks	Guidance
6(b)	Counting/outputting the number of double/repeated/pairs of letters in a word	1	

Question	Answer	Marks	Guidance
7(a)	One from: • So the data is stored permanently // provides a non-volatile copy • So the data is not lost if the machine/program is switched off/crashes • So the data can be used again later // to provide a backup • So the data can be transported to a different (offline) computer // so the data can be shared	1	
7(b)	One mark each • Declaration of an appropriately named variable • Correct statement to open <code>Names.txt</code> for reading • Correct statement to read data from the file into a variable • Correct statement to close <code>Names.txt</code> For example: <pre>DECLARE Name : STRING OPENFILE "Names.txt" FOR READ READFILE "Names.txt", Name CLOSEFILE "Names.txt"</pre>	4	Ignore case Filename and variable name must be consistent throughout If <code>Names.txt</code> not used, or quotes are missing, penalise once and FT Accept single or double quotes for the filename

Question	Answer	Marks	Guidance
8(a)	One mark for each correct gate, with the correct inputs as shown. 	5	

Question	Answer	Marks	Guidance																																				
8(b)	Four marks for eight correct outputs Three marks for six or seven correct outputs Two marks for four or five correct outputs One mark for two or three correct outputs <table border="1"> <thead> <tr> <th>A</th><th>B</th><th>C</th><th>Z</th></tr> </thead> <tbody> <tr><td>0</td><td>0</td><td>0</td><td>1</td></tr> <tr><td>0</td><td>0</td><td>1</td><td>0</td></tr> <tr><td>0</td><td>1</td><td>0</td><td>1</td></tr> <tr><td>0</td><td>1</td><td>1</td><td>1</td></tr> <tr><td>1</td><td>0</td><td>0</td><td>1</td></tr> <tr><td>1</td><td>0</td><td>1</td><td>1</td></tr> <tr><td>1</td><td>1</td><td>0</td><td>1</td></tr> <tr><td>1</td><td>1</td><td>1</td><td>0</td></tr> </tbody> </table>	A	B	C	Z	0	0	0	1	0	0	1	0	0	1	0	1	0	1	1	1	1	0	0	1	1	0	1	1	1	1	0	1	1	1	1	0	4	emboldened parts given in question
A	B	C	Z																																				
0	0	0	1																																				
0	0	1	0																																				
0	1	0	1																																				
0	1	1	1																																				
1	0	0	1																																				
1	0	1	1																																				
1	1	0	1																																				
1	1	1	0																																				

Question	Answer	Marks	Guidance																											
9(a)	One mark for every two correct data types <table><tr><th>field</th><th>data type</th><th>description</th></tr><tr><td>PartID</td><td>text</td><td>uniquely identifies the car part with letters and numbers</td></tr><tr><td>PartName</td><td>text</td><td>name of the car part, for example windscreen wiper</td></tr><tr><td>CarType</td><td>integer/text</td><td>four-digit number code to represent the car type</td></tr><tr><td>Price</td><td>real</td><td>selling price to 2 decimal places</td></tr><tr><td>Size</td><td>text</td><td>specifies the size if relevant, otherwise would say 'one size'</td></tr><tr><td>Colour</td><td>character</td><td>single letter code for the colour of the item</td></tr><tr><td>NumberInStock</td><td>Integer</td><td>the number of car parts in stock</td></tr><tr><td>InStock</td><td>Boolean/text/character/integer</td><td>whether or not the part is in stock</td></tr></table>	field	data type	description	PartID	text	uniquely identifies the car part with letters and numbers	PartName	text	name of the car part, for example windscreen wiper	CarType	integer/text	four-digit number code to represent the car type	Price	real	selling price to 2 decimal places	Size	text	specifies the size if relevant, otherwise would say 'one size'	Colour	character	single letter code for the colour of the item	NumberInStock	Integer	the number of car parts in stock	InStock	Boolean/text/character/integer	whether or not the part is in stock	4	Emboldened parts given in question Ignore case
field	data type	description																												
PartID	text	uniquely identifies the car part with letters and numbers																												
PartName	text	name of the car part, for example windscreen wiper																												
CarType	integer/text	four-digit number code to represent the car type																												
Price	real	selling price to 2 decimal places																												
Size	text	specifies the size if relevant, otherwise would say 'one size'																												
Colour	character	single letter code for the colour of the item																												
NumberInStock	Integer	the number of car parts in stock																												
InStock	Boolean/text/character/integer	whether or not the part is in stock																												

Question	Answer	Marks	Guidance
9(b)	One mark each - At least two correct fields in <code>SELECT</code> row - Remaining correct field in <code>SELECT</code> row - Correct FROM <code>CAR_PARTS</code> - Correct WHERE <code>PartName = "brake pads";</code> Correct code: <pre>SELECT PartID, CarType, NumberInStock FROM CAR_PARTS WHERE PartName = "brake pads"; // PartName = 'brake pads';</pre>	4	Ignore case on field names, but spelling must match names in table. Field names in <code>SELECT</code> line can be in any order. If space in field/table name, penalise once and FT. Allow <code>brake_pads</code>, <code>BrakePads</code>, <code>BrakePad</code> for MP4. Ignore minor spelling errors e.g. <code>break_pads</code>
9(c)	One mark each - There is an alternative field <code>NumberInStock</code> ... a value of 0 in this field indicates the item is out of stock // ... a positive value in this field indicates the item is in stock // ... this field indicates the quantity in stock	2	

PUBLISHED

Question	Answer	Marks	Guidance
10	Use the tables for AO2 and AO3 below to award a mark in a suitable band using a best fit approach, then add up the total. Marks are available for: • AO2 (maximum 9 marks) • AO3 (maximum 6 marks) Data structures required with names as given in the scenario: Arrays or lists <code>Rainfall[]</code> Requirements (techniques) R1 Declares of variables and array, initialises array, inputs daily rainfall in mm for a year and stores it in the array (declarations, initialisation, iteration, input, output). R2 Calculates the total rainfall for the year in cm rounded to 2 d.p., the mean average rainfall in mm rounded to 4 d.p., the number of days with no rainfall and the longest period of days with no rainfall (totalling, counting, iteration, rounding, selection, finding max). R3 Outputs the total rainfall for the year in cm, the average rainfall, the number of days with no rainfall and the longest period of days with no rainfall. Determines if a drought occurred and outputs the result (output, selection).	15	

Question	Answer	Marks	Guidance
10	Example 15-mark answer in pseudocode: <pre>// array and variable declaration DECLARE Rainfall : ARRAY[1:365] OF REAL DECLARE Index : INTEGER DECLARE TotalRain : REAL DECLARE AverageRain : REAL DECLARE NoRain : INTEGER DECLARE DryDays : INTEGER DECLARE MaxDryDays : INTEGER // initialising array FOR Index ← 1 TO 365 Rainfall[Index] ← 0 NEXT Index // daily input of rainfall FOR Index ← 1 TO 365 OUTPUT "Input the rainfall measurement for day ", Index INPUT Rainfall[Index] NEXT Index // finding the total and average rainfall TotalRain ← 0 FOR Index ← 1 TO 365 TotalRain ← TotalRain + Rainfall[Index] NEXT Index // average daily rainfall to 4dp AverageRain ← ROUND(TotalRain/365, 4) // total rainfall in cm to 2dp TotalRain ← ROUND(TotalRain/10, 2)</pre>		

Question	Answer	Marks	Guidance
10	<pre>// counting the number of days with no rain NoRain ← 0 FOR Index ← 1 TO 365 IF Rainfall[Index] = 0 THEN NoRain ← NoRain + 1 ENDIF NEXT Index // finding the longest number of consecutive rain free days IF NoRain > 0 THEN MaxDryDays ← 1 DryDays ← 1 FOR Index ← 1 TO 365-1 IF Rainfall[Index] = 0 AND Rainfall[Index + 1] = 0 THEN DryDays ← DryDays + 1 IF DryDays > MaxDryDays THEN MaxDryDays ← DryDays ENDIF ELSE DryDays ← 1 ENDIF NEXT Index ELSE MaxDryDays ← 0 DryDays ← 0 ENDIF</pre>		

Question	Answer	Marks	Guidance
10	<pre>// outputting the statistics with messages OUTPUT "The total rainfall for the year was ", TotalRain, " cm" OUTPUT "The average daily rainfall was ", AverageRain, " mm" OUTPUT "The total number of days with no rainfall was ", NoRain, " day(s) " OUTPUT "The longest period with no rainfall was ", MaxDryDays, " day(s) " // checking if there was a drought IF MaxDryDays >= 15 THEN OUTPUT "" OUTPUT "There was a drought this year because the longest period with no rainfall was 15 days or longer" ELSE OUTPUT "" OUTPUT "There was no drought this year, because the longest period with no rainfall was shorter than 15 days" ENDIF</pre>		

Marking Instructions in italics			
AO2: Apply knowledge and understanding of the principles and concepts of computer science to a given context, including the analysis and design of computational or programming problems			
0	1–3	4–6	7–9
No creditable response.	At least one programming technique has been used. <i>Any use of selection, iteration, counting, totalling, input and output.</i>	Some programming techniques used are appropriate to the problem. <i>More than one technique seen applied to the scenario, check the list of techniques needed.</i>	The range of programming techniques used is appropriate to the problem. <i>All criteria stated for the scenario have been covered by the use of appropriate programming techniques, check the list of techniques needed.</i>
	Some data has been stored but not appropriately. <i>Any use of variables or arrays or other language dependent data structures e.g. Python lists.</i>	Some of the data structures chosen are appropriate and store some of the data required. <i>More than one data structure used to store data required by the scenario.</i>	The data structures chosen are appropriate and store all the data required. <i>The data structures used store all the data required by the scenario.</i>

Marking Instructions in italics			
AO3: Provide solutions to problems by: evaluating computer systems making reasoned judgements presenting conclusions			
0	1–2	3–4	5–6
No creditable response.	Program seen without relevant comments.	Program seen with some relevant comment(s).	The program has been fully commented
	Some identifier names used are appropriate. <i>Some of the data structures used have meaningful names.</i>	The majority of identifiers used are appropriately named. <i>Most of the data structures used have meaningful names.</i>	Suitable identifiers with names meaningful to their purpose have been used throughout. <i>All the data structures used have meaningful names.</i>
	The solution is illogical.	The solution contains parts that may be illogical.	The program is in a logical order.
	The solution is inaccurate in many places. <i>Solution contains few lines of code with errors that attempt to perform a task given in the scenario.</i>	The solution contains parts that are inaccurate. <i>Solution contains lines of code with some errors that logically perform tasks given in the scenario. Ignore minor syntax errors.</i>	The solution is accurate. <i>Solution logically performs all the tasks given in the scenario. Ignore minor syntax errors.</i>
	The solution attempts at least one of the requirements. <i>Solution contains lines of code that attempt at least one task given in the scenario.</i>	The solution attempts to meet most of the requirements. <i>Solution contains lines of code that attempt most tasks given in the scenario.</i>	The solution meets all the requirements given in the question. <i>Solution performs all the tasks given in the scenario.</i>