
MATHEMATICS

9709/43

Paper 4

October/November 2016

MARK SCHEME

Maximum Mark: 50

Published

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the October/November 2016 series for most Cambridge IGCSE[®], Cambridge International A and AS Level components and some Cambridge O Level components.

Page 2	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – October/November 2016	9709	43

Mark Scheme Notes

Marks are of the following three types:

M Method mark, awarded for a valid method applied to the problem. Method marks are not lost for numerical errors, algebraic slips or errors in units. However, it is not usually sufficient for a candidate just to indicate an intention of using some method or just to quote a formula; the formula or idea must be applied to the specific problem in hand, e.g. by substituting the relevant quantities into the formula. Correct application of a formula without the formula being quoted obviously earns the M mark and in some cases an M mark can be implied from a correct answer.

A Accuracy mark, awarded for a correct answer or intermediate step correctly obtained. Accuracy marks cannot be given unless the associated method mark is earned (or implied).

B Mark for a correct result or statement independent of method marks.

- When a part of a question has two or more “method” steps, the M marks are generally independent unless the scheme specifically says otherwise; and similarly when there are several B marks allocated. The notation DM or DB (or dep*) is used to indicate that a particular M or B mark is dependent on an earlier M or B (asterisked) mark in the scheme. When two or more steps are run together by the candidate, the earlier marks are implied and full credit is given.
- The symbol ∇ implies that the A or B mark indicated is allowed for work correctly following on from previously incorrect results. Otherwise, A or B marks are given for correct work only. A and B marks are not given for fortuitously “correct” answers or results obtained from incorrect working.
- Note: B2 or A2 means that the candidate can earn 2 or 0.
B2/1/0 means that the candidate can earn anything from 0 to 2.

The marks indicated in the scheme may not be subdivided. If there is genuine doubt whether a candidate has earned a mark, allow the candidate the benefit of the doubt. Unless otherwise indicated, marks once gained cannot subsequently be lost, e.g. wrong working following a correct form of answer is ignored.

- Wrong or missing units in an answer should not lead to the loss of a mark unless the scheme specifically indicates otherwise.
- For a numerical answer, allow the A or B mark if a value is obtained which is correct to 3 s.f., or which would be correct to 3 s.f. if rounded (1 d.p. in the case of an angle). As stated above, an A or B mark is not given if a correct numerical answer arises fortuitously from incorrect working. For Mechanics questions, allow A or B marks for correct answers which arise from taking g equal to 9.8 or 9.81 instead of 10.

Page 3	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – October/November 2016	9709	43

The following abbreviations may be used in a mark scheme or used on the scripts:

AEF/OE Any Equivalent Form (of answer is equally acceptable) / Or Equivalent

AG Answer Given on the question paper (so extra checking is needed to ensure that the detailed working leading to the result is valid)

CAO Correct Answer Only (emphasising that no “follow through” from a previous error is allowed)

CWO Correct Working Only – often written by a ‘fortuitous’ answer

ISW Ignore Subsequent Working

SOI Seen or implied

SR Special Ruling (detailing the mark to be given for a specific wrong solution, or a case where some standard marking practice is to be varied in the light of a particular circumstance)

Penalties

MR –1 A penalty of MR –1 is deducted from A or B marks when the data of a question or part question are genuinely misread and the object and difficulty of the question remain unaltered. In this case all A and B marks then become “follow through $\frac{1}{2}$ ” marks. MR is not applied when the candidate misreads his own figures – this is regarded as an error in accuracy. An MR –2 penalty may be applied in particular cases if agreed at the coordination meeting.

PA –1 This is deducted from A or B marks in the case of premature approximation. The PA –1 penalty is usually discussed at the meeting.

Page 4	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – October/November 2016	9709	43

1	(i)	$PE \text{ gain} = 50g \times 3.5 (=1750)$ $[WD = 50g \times 3.5 + 25 \times 3.5]$ Work done = 1837.5 J or 1840 J	B1 M1 A1	[3]	For using $WD = PE \text{ gain} + WD \text{ against resistance}$
	(ii)	$[P = 1837.5/2]$ or $[P/v = 50g + 25 \text{ and } 3.5=2v]$ Power = 919 W	M1 A1	[2]	For using $P = WD/t$ or for using $P = Fv$ and $s = vt$
2		$T_A \cos 50^\circ - T_B \cos 10^\circ = 0$ and $T_A \sin 50^\circ - T_B \sin 10^\circ - 20g = 0$ Tension in PA is 306 N Tension in PB is 200 N	M1 M1 A1 M1 A1	[5]	For resolving horizontally For resolving vertically For solving equations to find T_A and T_B
		Alternative (Lami's Theorem) $[T_A/\sin 80^\circ = T_B/\sin 140^\circ = 20g/\sin 140^\circ]$ $[T_A=20g \sin 80^\circ/\sin 140^\circ]$ Tension in PA is 306 N $[T_B=20g \sin 140^\circ/\sin 140^\circ]$ Tension in PB is 200 N	M1 M1 A1 M1 A1	[5]	For applying Lami's Theorem For solving for T_A For solving for T_B

Page 5	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – October/November 2016	9709	43

3	(i)	$[7g - T = 7a \text{ and } T - 3g = 3a]$ or $[7g - 3g = 10a]$ Acceleration is 4 ms^{-2} $[v^2 = 0 + 2 \times 4 \times 0.4] (v^2 = 3.2)$ Speed is 1.79 ms^{-1}	M1 A1 M1 A1	[4]	For applying Newton's second law to P and to Q or for using $m_P g - m_Q g = (m_P + m_Q)a$ For using $v^2 = u^2 + 2as$
	(ii)	$[0 = 3.2 + 2 \times (-g) \times s] (s = 0.16)$ $0.16 + 0.4 = 0.56$ So particle Q does not come to rest before it reaches the pulley Alternative $[v^2 = 3.2 + 2 \times (-g) \times 0.1]$ $v = \sqrt{1.2} (= 1.10)$ So particle Q does not come to rest before it reaches the pulley	M1 A1 M1 A1	[2] [2]	For using $0 = u^2 + 2(-g)s$ For using $v^2 = u^2 + 2(-g)(0.1)$
4	(i)	$s_A = \frac{1}{2}g \times 2.5^2 (= 31.25)$ $[s_B = 20 \times 1.5 - \frac{1}{2}g \times 1.5^2] (= 18.75)$ $\frac{1}{2}g \times 2.5^2 + 20 \times 1.5 - \frac{1}{2}g \times 1.5^2$ Height is 50m AG	B1 M1 A1	[3]	For using $s = ut + \frac{1}{2}at^2$
	(ii)	$50 = 0.5gt_A^2 \quad (t_A = 3.16)$ $t_B = \sqrt{10 - 1} = 2.16$ To top, $0^2 = 20^2 - 2gs_B \quad \rightarrow s_B = 20$ To top, $[0 = 20 - gt_B] \quad \rightarrow t_B = 2$ Downwards, $[s_B = \frac{1}{2}g(0.16)^2] (= 0.13)$ Total distance is 20.1 m	B1 B1 B1 M1 A1	[5]	For using $s = \frac{1}{2}at^2$ For using $v = u + at$ to find time to top for B and $s = \frac{1}{2}at^2$ to find downwards distance for B

Page 6	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – October/November 2016	9709	43

5	(i)	$6t - 0.3t^2 = 0 \rightarrow t = 20$ (or 0) $[s = 6t^2/2 - 0.3t^3/3 (+C)]$ $[s = 6(20)^2/2 - 0.3(20)^3/3]$ Distance OX is 400 m	B1 M1 DM1 A1		For integrating $v(t)$ to obtain $s(t)$ For evaluating $s(t)$ when $v=0$
	(ii)	$[v = kt - 6t^2 (+C)]$ $[s = kt^2/2 - 6t^3/3]$ $[400 = 0.5k \times 10^2 - 2 \times 10^3]$ $k = 48$	M1* M1* DM1 A1		For integrating $a(t)$ to obtain $v(t)$ For integrating $v(t)$ to obtain $s(t)$ and for using $s(0) = 0$ For using $t = 10$ and $s = 400$ to form equation in k
6	(i)	Driving force = $160/5$ (= 32 N) $[160/5 - 20 = m \times 0.15]$ Total mass is 80 kg	B1 M1 AG A1		For using Newton's Second Law
	(ii)	$[300/v - 20 - 80g \sin 2^\circ = 0]$ Speed is 6.26 ms^{-1}	M1 AG A1		For resolving up hill
	(iii)	Driving force = $300/(0.9 \times 6.26)$ (= 53.2 N) $300/(0.9 \times 6.26) - 20 - 80g \sin 2^\circ = 80a$ Acceleration is 0.0666 ms^{-2}	B1 M1 A1 A1		For using Newton's Second Law

Page 7	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – October/November 2016	9709	43

7	(i) $R = 50g \cos 10^\circ$ and $F = 50g \sin 10^\circ$ $\mu \geq 0.176$	B1 B1	[2]	$\mu \geq F \div R$ Allow $\mu \geq \tan 10^\circ$
	(ii) PE loss = $50g \times d \sin 10^\circ$ WD against friction = $0.19 \times 50g \cos 10^\circ \times d$ $50 \times 5 + 50g \times 10 \sin 10^\circ - 0.19 \times 50g \cos 10^\circ \times 10 = 0.5 \times 50v^2$ Speed is 2.70 ms^{-1}	B1 B1 M1 A1 A1	[5]	$d = 5$ or $d = 10$ $d = 5$ or $d = 10$ For using WD by 50 N force + PE loss – WD against friction = KE gain SC for candidates using Newton's Second law: max 2/5 B1 $v = 2.94 \text{ ms}^{-1}$ after 5 m B1 Speed is 2.70 ms^{-1}
	(iii) $50g \sin 20^\circ - 0.19 \times 50g \cos 20^\circ = 50a$ Acceleration is 1.63 ms^{-2}	M1 A1	[2]	For using Newton's Second Law